INLET WATER PUMP





Our inlet water pumps are close-coupled self-priming centrifugal pumps with built-in ejector systems, designed to remain primed even in the presence of water-dissolved gases.

The extensive use of the pressed stainless steel ensures high-performance, durable and lightweight pump. Suitable for use with drinking water.

APPLICATIONS

- Water distribution
- Pressure boosting
- Irrigation
- Washing
- Rain water collection
- Swimming pools
- Fountains

PUMP MATERIALS

- Pump body: Stainless steel
- Impeller: Stainless steel
- Diffuser: Technopolymer
- Ejector: Technopolymer
- Seal housing: Stainless steel
- Mechanical seal: Ceramic / Carbon / EPDM
- Fill and drain plugs: Nickel-plated brass
- Elastomers: EPDM

TECHNICAL DATA	INLET WATER PUMP
Product Code	DSA002
Delivery	Up to 4.2m³/h
Head	Up to 53m
Power Supply	Single-phase and three- phase 50 and 60Hz
Power	0.37kW to 1.1kW
Max. Operating Pressure	8 bar
Max. Total Lift	8m

	INLET WATER PUMP
Max. Ambient Temperature	40°C
Temperature of Pumped Liquid	-10°C to +40°C
Insulation Class	F
Protection	IP55

©: www.mfc-international.com

L: +44 (0) 1443 433 075