

Flexible Packer Systems



Our new flexible packer replaces previous LONG and FLEX packer designs with a single solution. This new design combines greater reinforcement with ease of use for an effective all-in-one solution. The packer is a sectional repair method for all types of drainage pipes.

- Snap on/off wheels can be quickly and easily removed
- Highly flexible bypass pipe simplifies insertion of the packer while providing strong support when pushing the packer along the pipe
- The bypass lock with its protected thread allows you to configure the packer for bypass or non-flow use
- Product weight has been reduced through the use of new lighter materials, simplifying handling and transport of larger packers

Part Number	Size		Size Usage Range (mm)		Deflated Packer (mm)		Rubber Body Length (mm)	Weight (kg)	Inflation Pressure (bar)	Bypass Diameter (Female) (inch)
		(m)	Min Dia	Max Dia	Diameter	Length				
FP0001	10-15 F	1	100	150	65	1120	1050	2.2	2.5	N/A
FP0002	10-15 F	1.5	100	150	65	1620	1550	2.6	2.5	N/A
FP0003	10-15 F	2	100	150	65	2120	2050	2.9	2.5	N/A
FP0004	10-15 F	2.5	100	150	65	2620	2550	3.4	2.5	N/A
FP0005	10-15 F	3	100	150	65	3120	3050	4.3	2.5	N/A
FP0006	10-15 F	4	100	150	65	4120	4050	5.1	2.5	N/A
FP0007	10-15 F	5	100	150	65	5120	5050	6.1	2.5	N/A
FP0008	15-25 F	1	150	250	114	1180	1080	8.5	2	2
FP0009	15-25 F	1.5	150	250	114	1680	1580	10	2	2
FP0010	15-25 F	2	150	250	114	2180	2080	11.5	2	2
FP0011	15-25 F	2.5	150	250	114	2680	2580	13	2	2
FP0012	15-25 F	3	150	250	114	3180	3080	15	2	2
FP0013	15-25 F	4	150	250	114	4180	4080	17.5	2	2
FP0014	15-25 F	5	150	250	114	5180	5080	21.9	2	2
FP0015	20-30F	1	200	300	145	1180	1080	5.1	1.5	2
FP0016	20-30F	1.5	200	300	145	1680	1580	5.9	1.5	2
FP0017	20-30F	2	200	300	145	2180	2080	6.7	1.5	2
FP0018	20-30F	2.5	200	300	145	2680	2580	8.8	1.5	2
FP0019	20-30F	3	200	300	145	3180	3080	11	1.5	2
FP0020	20-30F	4	200	300	145	4180	4080	14	1.5	2
FP0021	20-30F	5	200	300	145	5180	5080	19	1.5	2



Flexible Packer Systems

Part Number	Size		Size Usage Range (mm)		Deflated Packer (mm)		Rubber Body Length (mm)	Weight (kg)	Inflation Pressure (bar)	Bypass Diameter (Female) (inch)
		(m)	Min Dia	Max Dia	Diameter	Length				
FP0022	30-40 F	1	300	400	245	1280	1080	20	1.5	3
FP0023	30-40 F	1.5	300	400	245	1780	1580	22.6	1.5	3
FP0024	30-40 F	2	300	400	245	2280	2080	26	1.5	3
FP0025	30-40 F	2.5	300	400	245	2780	2580	30	1.5	3
FP0026	30-40 F	3	300	400	245	3280	3080	34	1.5	3
FP0027	30-40 F	4	300	400	245	4280	4080	43	1.5	3
FP0028	30-40 F	5	300	400	245	5280	5080	49	1.5	3
FP0029	40-50 F	1	400	500	340	1300	1080	34	1.2	3
FP0030	40-50 F	1.5	400	500	340	1800	1580	37	1.2	3
FP0031	40-50 F	2	400	500	340	2300	2080	42	1.2	3
FP0032	40-50 F	2.5	400	500	340	2800	2580	51	1.2	3
FP0033	40-50 F	3	400	500	340	3300	3080	56	1.2	3
FP0034	40-50 F	4	400	500	340	4300	4080	62	1.2	3
FP0035	40-50 F	5	400	500	340	5300	5080	70	1.2	3
FP0036	45-60F	1	450	600	340	1340	1120	36	1.2	3
FP0037	45-60F	1.5	450	600	340	1840	1620	38	1.2	3
FP0038	45-60F	2	450	600	340	2340	2120	43.5	1.2	3
FP0039	45-60F	2.5	450	600	340	2840	2620	53	1.2	3
FP0040	45-60F	3	450	600	340	3340	3120	57.5	1.2	3
FP0041	45-60F	4	450	600	340	4340	4120	63.5	1.2	3
FP0042	45-60F	5	450	600	340	5340	5120	71	1.2	3
FP0043	50-60F	1	500	600	405	1340	1120	40	1	3
FP0044	50-60F	1.5	500	600	405	1840	1620	43.5	1	3
FP0045	50-60F	2	500	600	405	2340	2120	48	1	3
FP0046	50-60F	2.5	500	600	405	2840	2620	56	1	3
FP0047	50-60F	3	500	600	405	3340	3120	59	1	3
FP0048	50-60F	4	500	600	405	4340	4120	65	1	3
FP0049	50-60F	5	500	600	405	5340	5120	74	1	3